



DECORATIVE WATER-BASED INTERIOR PRODUCT GROUP

BETEK CRYSTAL Sandy, Metallic Effect

PRODUCT DESCRIPTION

Water-based, sandy-textured, glossy, decorative top coat interior paint.

APPLICATION

Ensure the application surface is smooth, stable, dry and self-supporting. Smooth and flat the surface with Betek Interior Paste. Smooth with emery paper 24 hours after the application of Betek Interior Paste. Clean the sand dust fully using a damp cloth and apply Betek Lux Primer on the pasted surface using a roller. For surface preparation, never use satin plaster due to its weak and dust-generating texture.

Tape the edges of the application surface with the masking tape. Apply following the respective technique for the selected pattern using a plastic paint cutting-in brush with the suitable soft bristle. Different patterns may be obtained with different application methods. Betek Crystal is ready to use and the product should not be thinned.

BETEK CRYSTAL APPLICATION OPTIONS

Betek Crystal Diagonal Pattern - Vertical Line Pattern - Horizontal Line Pattern: Take Betek Crystal on an Effect Brush and apply it in parallel lines following each other starting from the top corner. After 5-10 minutes, comb the surface with a clean, soft, wide brush in the shape of the final design.

Betek Crystal Mixed Pattern: Take Betek Crystal on an Effect Brush, apply in the shape of cross, plus or half moon starting from the top corner of the surface. After 5-10 minutes, comb the surface with a clean, soft, wide brush in the shape of the final design.

THINNING

Ready to use. Do not thin. Mix the product thoroughly before application.

DRYING TIME (at 20°C, 65% RH)

First drying: 30 minutes

Waiting period between coats: 4-6 hours

Final drying: 24 hours (drying time may increase at higher relative humidity and lower temperatures).

CONSUMPTION

165-210ml/m² in a single coat depending on the type, absorption and structure of the application surface. 4.5-6m² of surface can be painted in a single coat with 1L. Perform a controlled sample run to estimate the precise consumption.

PACKAGING

2.5L

STORAGE

May be stored for 3 years in its unopened packaging in a cool and dry environment protected against frost and direct sunlight. Close the lid air-tight immediately after application.

Precautionary Statement

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of the reach of children.

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapor/spray.

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

This technical sheet is prepared based on laboratory data at normal conditions. Consult technical personnel for details that are not provided above. Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change this information. Where necessary, please refer to Material Safety Data Sheets for more information on health, safety and handling risks and precautions associated with the products.

This product is manufactured by Betek A.Ş. having the certificate of conformity to the standards TS EN ISO 9001, TS



EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002.