



DECORATIVE WATER-BASED INTERIOR PRODUCT GROUP

BETEK CEILING PLASTIC

DESCRIPTION

Acrylic copolymer emulsion-based, decorative, matt white ceiling paint for interior surfaces.

SPECIFICATIONS

Betek Ceiling Plastic is a water-based paint with a high level of breathability. Matt and smooth finish. Adheres perfectly to surfaces. Features a high covering power. No blistering and flaking.

APPLICATION SURFACES

Preferred to be used on satin plaster, putty, plasterboard surfaces and old painted or primed interior ceiling surfaces with no dusting behavior.

APPLICATION

Ensure the application surface is smooth, secure and in a well condition to hold the primer and the top-coat paint. Clean all types of stain, dust, block grease, loose layers and make the required surface corrections. Comply with the defined setting periods on concrete, brute concrete and new plastered surfaces (28 days).

Apply Betek Gypsum Primer on absorbing and high dust generating surfaces like lime, plaster and whitewash before combing and polishing. Ensure the ambient and the surface temperature is between +5°C and +30°C during the application and until the product is fully dry, and protect the surfaces against frost. Apply using a brush, a roller or a sprayer.

You can access the MSDS and TDS forms including the information regarding detailed application, healthy-safety-handling risks and precautions on www.betekexport.com.

For airless spraying:

Pressure	: 140 bar
Nozzle Angle	: 50°
Nozzle Size (inch)	: 0.019"
Thinning (Water)	: 10-15 % (Volume)

THINNING

Recommended to be applied in two coats after thinning by 20% with clean water in brush and roller applications. Recommended to be applied in one coat provided that the sufficient film thickness is achieved after thinning by 10-15% with clean water in airless spraying.

DRYING TIME (at 20°C, 65% HR):

Touch dryness: 1 hours

Resting period between coats: 6 hours

Final drying: 24 hours (drying time can increase at higher relative humidity and lower temperature values)

CONSUMPTION

7-10 m² single coat per kilogram depending on the type, absorbency and structure of the application surface. Perform a controlled sample run to estimate the precise consumption.

STORAGE

May be stored for 3 years in its unopened packaging in a cool and dry environment protected against frosting and direct sunlight. Close the package right after application in an air-tight manner.

PACKAGING

25 Kg, 20 Kg, 10 Kg, 3.5 Kg

HAZARD DESCRIPTION

Xi Irritating.

Hazard statements

H317 May cause an allergic skin reaction

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.



P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment (see on this label).

P363 Wash contaminated clothing before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations

This technical sheet is prepared based on laboratory data under normal conditions, consult to technical personnel for details that are not provided above. Otherwise, the manufacturing company cannot be held responsible for the failures that may arise due to lack of knowledge. Our company reserves the right to change this information.

This product is manufactured by Betek A.Ş. having the certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002.