



DECORATIVE WATER-BASED INTERIOR PRODUCT GROUP

BETEK GYPSUM PRIMER

PRODUCT DESCRIPTION

Ready-to-use, copolymer emulsion resin-based, transparent interior plaster primer.

SPECIFICATIONS

Forms a bridge between the paint and the surface. Enables the top-coat paint layer to integrate with the application surface by penetrating deep into the application surface with this high penetration ability. Prevents the paint to dry early especially during hot weather conditions and decreases paint consumption since it prevents surface absorption. Prevents surface absorption on plaster surfaces that are challenging for the painters and prepares the surface for painting.

APPLICATION SURFACES

Betek Gypsum Primer is applied on plaster, lime, whitewash, silicone based paint surfaces that lost their quality and highly absorbing and/or high dust generating surfaces like aerated concrete.

APPLICATION

Ensure the application surface is smooth, secure and in a well condition to hold the primer and the top-coat paint. Clean all types of stain, dust, block grease, loose layers and make the required surface corrections. Comply with the defined setting periods on concrete, brute concrete and new plastered surfaces (28 days).

Apply the transparent primer on plaster or similar surfaces only after they are sanded and dusted with a moist cloth/moist car wash brush/broom. Ensure the ambient and the surface temperature is between +5°C and +30°C during the application and until the product is fully dry, and protect the surfaces against frost. Apply Betek Gypsum Primer as a single coat using a brush or a roller without combing/polishing (by rolling the roller in one direction once) in a way that will not create a glassy thin film layer on the surface. Dull the surface with sand paper if a glassy surface is created. Avoid airless spraying method.

You can access the MSDS and TDS forms including the information regarding detailed application, healthy-safety-handling risks and precautions on www.betekexport.com.

WARNING:

Pigment Primers: Use Betek Primer as primer/transition primer on wall surfaces that are both primed and painted with water-solvent based paints. Since the binder will be absorbed when such primers are applied to absorbing and high dust generating surfaces like plaster, lime, whitewash and aerated concrete, there will be dusty appearance on the surface and problems will be seen.

THINNING

Ready to use.

DRYING TIME (at 20°C, 65% HR):

Touch dryness: 1 hours

Paint application: 6 hours (drying time can increase at higher relative humidity and lower temperature values)

CONSUMPTION

8-12.5 m² single coat per liter depending on the type, absorbency and structure of the application surface. Perform a controlled sample run to estimate the precise consumption.

STORAGE

May be stored for 3 years in its unopened packaging in a cool and dry environment protected against frosting and direct sunlight. Close the package right after application in an air-tight manner.

PACKAGING

20 L, 5 L

HAZARD DESCRIPTION

Xi Irritating.

Hazard statements

H317 May cause an allergic skin reaction



Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment (see on this label).

P363 Wash contaminated clothing before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations

This technical sheet is prepared based on laboratory data under normal conditions, consult to technical personnel for details that are not provided above. Otherwise, the manufacturing company cannot be held responsible for the failures that may arise due to lack of knowledge. Our company reserves the right to change this information.