



DECORATIVE WATER-BASED EXTERIOR PRODUCT GROUP

BETEK EXTERIOR PASTE

PRODUCT DESCRIPTION

Acrylic copolymer emulsion-based, flexible exterior filler and surface correction paste.

SPECIFICATIONS

Acts as a filler in filling the gaps formed after cleaning old-painted and bloated exterior surfaces and in correcting existing mistakes. Prevents shrinkage cracks to rise up to the top-coat thanks to its flexibility. Resistant to water and moisture. Creates a very secure and even surface. All types of paint can be applied provided that the suitable primer is used. Low absorbency, low paint consumption. Does not prevent breathability of the surfaces. thus providing savings in both time and labor.

APPLICATION SURFACES

Can be used safely in correcting concrete and mineral-plastered, old-painted and rough surfaces on exterior walls and in filling shrinkage cracks.

APPLICATION

Ensure the application surface is secure, dry, clean and self-supporting. Remove all types of stain, dust, block grease and loose layers. Wait for the setting period (28 days) on concrete, brute concrete, new plastered surfaces and clean the loose plaster particles with scraper or similar methods. Add fresh white or gray cement into Betek Exterior Paste and mix after blending it with water that is 20% of its weight for cement-based surfaces that will be painted for the first time. Apply the prepared paste onto the surface with a spatula, a flexible steel trowel or a sprayer. Apply the second coat after the first coat is applied and dried (24 hours) (Recommended to be applied with maximum 1 mm thickness each time). Consume maximum within 1 hour after adding the cement. Be careful to ensure that ambient and surface temperature stays between +5°C and +30°C throughout the application. Do not apply at windy environments and under direct sunlight. Prefer shady wall if required to be applied in hot weather conditions above +30°C and abstain from application from 10:00 AM to 04:00 PM.

You can access the MSDS and TDS forms including the information regarding detailed application, healthy-safety-handling risks and precautions on www.betekexport.com.

WARNINGS

Surfaces requiring Repair Mortar:

Apply Betek Stako for 0-10 mm surface leveling and correcting. Recommended to use 1 kg Betek 1 + 4 kg Water for thinning.

Apply glass-fiber mesh with 10 cm width along the crack if the crack continues as a straight line on the surface and with 10 cm at all joints throughout the surface if there are numerous cracks on the surface. Ensure the glass-fiber mesh is applied as close to the exterior surface as 1/3 of the total thickness of the surface correction and leveling material.

Protect the surfaces from extreme dew and rain especially during the period between cement-based surface correction and repair paste application and final coat. Otherwise, white spots will be formed. In such a case, moisture the surface with a car wash brush and apply 1 unit of water-based siloxane base surface impregnated material + 1 unit of water mixture.

Airless Spraying

Pressure : 200 bar
Nozzle Angle : 50°
Nozzle Size (inch) : 0.035"
Thinning (Water) : Ready to use. Never thin.

THINNING

Ready to use. Never thin.

DRYING TIME (at 20°C, 65% HR):

Touch drying : 2-3 hours
Final drying : 24 hours

CONSUMPTION

0.7-1.5 m² single coat per kilogram depending on the type, absorbency and structure of the application surface. Perform a controlled sample run to estimate the precise consumption.

STORAGE

May be stored for 3 years in its unopened packaging in a cool and dry environment protected against frosting and direct sunlight. Close the package right after application in an air-tight manner.

PACKAGING

25 L/10 L/4 L

HAZARD DESCRIPTION

Xi Irritating.

Hazard statements

H317 May cause an allergic skin reaction

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment (see on this label).

P363 Wash contaminated clothing before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations

This technical sheet is prepared based on laboratory data under normal conditions, consult to technical personnel for details that are not provided above. Otherwise, the manufacturing company cannot be held responsible for the failures that may arise due to lack of knowledge. Our company reserves the right to change this information.