



## DECORATIVE SYNTHETIC PRODUCT RANGE

# Betek Floor Paint

### PRODUCT DESCRIPTION

Betek Floor Paint is a modified alkyd resin based aroma-free top coat wooden paint with high covering ability.

### SPECIFICATIONS

- MODIFIED ALKYD RESIN BASED, WOOD TOP COAT PAINT
- DOES NOT CONTAIN LEAD
- HIGH COVERING ABILITY
- EASE OF APPLICATION
- AROMA-FREE

### SURFACE PREPARATION

Surfaces on which Betek Floor Paint is to be applied must be cleaned from all grease, wood dusts, old paint and varnish residues. No resin must be present at new wooden surfaces. In order to protect the wooden surface, after new wooden surfaces are cleaned of dust and dirt with emery paper Betek Impregnation Care should be applied. After 24 hours, Betek Floor Paint should be applied in two coatings. Moisture of the wood must be below 18%.

### DENSITY

0,98±0,02 g/ml

### APPLICATION SURFACE

It is used on wooden floor and surfaces.

### THINNING RATIO

It is thinned by 5-10% with Betek Synthetic Thinner.

### APPLICATION TEMPERATURE

Must be between +5°C to +30°C.

### APPLICATION EQUIPMENT

Brush and roller must be used.

### NUMBER OF COATS

Betek Floor Paint should be applied as 2 coats.

Before commencing application, the packaging must be stirred thoroughly.

### DRYING TIME

Through drying time varies according to relative humidity and temperature and is 12 hours max.(20°C) Allow at least 24 hours between the coats. (At higher relative humidity and lower temperature, drying time may be longer.)

### EXPENDITURE

Varying to type, absorptivity and structure of the wooden application surface, approximately 8-12 m2 area can be painted as single coat with 1 liter of paint. There may be expenditure and color variations in accordance with the state of the application surface, number of coats and method of application. For exact expenditure, controlled sample study must be made.

### STORAGE

It is 3 years in cool and dry environment, in original and unopened container. In order to store the leftover paint within the packaging most safely, thinner must be added on paint until the surface of the paint is completely covered or the lid of the packaging must be sealed tightly and rolled 180° 1-2 times to be adjusted.



## **PACKAGING**

0,75lt , 2,5lt

## **DANGER DESCRIPTION**

Xn Harmful.

### **Danger warnings**

H226 Flammable liquid and vapor.

H304 May be fatal if swallowed and enters airways.

Contains 2-butanone oxime. May produce an allergic reaction.

### **Emergency Warning**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or consult a doctor/physician.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international legislation.

### **Hazard-determining components of labelling:**

Solvent naphtha (petroleum), medium aliph.

Since this technical page was prepared by taking into account general conditions, consult technical personnel for details not deemed sufficient. Otherwise, faults arising due to lack of information shall not encumber producer company with responsibilities. The right to change these information is reserved by our company.