

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.01.2015

Revision: 29.01.2015

#### **1** Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- Trade name: BETEK FLOOR PAINT
- · Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the preparation Synthetic paint.
- Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Betek Boya ve Kimya Sanayi A.S. G.O.S.B. Tembelova Alani 3200 Sokak No:3206 41400 Gebze/ Kocaeli/ Türkiye Tel: 00 90 262 678 30 00 Fax: 00 90 262 641 21 68
- · Further information obtainable from: R&D Department
- Emergency telephone number: 00 90 262 678 30 00

### **2** Hazards identification

- · Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

🗙 Xn; Harmful

- *R65: Harmful: may cause lung damage if swallowed.*
- R10: Flammable.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

• Classification system:

- The classification is according to the latest editions of the EU-lists, and extended by company and literature data.
- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



· Signal word Danger

Printing date 29.01.2015

Revision: 29.01.2015

Trade name: BETEK FLOOR PAINT

(Contd. of page 1)

· Hazard-determ	ining components of labelling:
Solvent naphtha	(petroleum), medium aliph.
· Hazard stateme	nts
H226 Flammab	le liquid and vapour.
H304 May be fa	ital if swallowed and enters airways.
	none oxime. May produce an allergic reaction.
· Precautionary s	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303+P361+P3	353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P405	
	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
• Other hazards	
· Results of PBT	and vPvB assessment
• <b>PBT:</b> Not appli	

• **vPvB:** Not applicable.

# 3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

CAS: 64742-88-7	Solvent naphtha (petroleum), medium aliph.	25-50%
EINECS: 265-191-7	🗙 Xn R65	
	🐼 Asp. Tox. 1, H304	
CAS: 64742-47-8	Distillates (petroleum), hydrotreated light	≤ 2.5%
EINECS: 265-149-8	🗙 Xn R65	
	🐼 Asp. Tox. 1, H304	
CAS: 108-88-3	toluene	≤ 2.5%
EINECS: 203-625-9	🗙 Xn R48/20-63-65; 🗙 Xi R38; 🐞 F R11 R67	
	� Flam. Liq. 2, H225; � Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; � Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 96-29-7	2-butanone oxime	≤ 2.5%
EINECS: 202-496-6	🗙 Xn R21-40; 🗙 Xi R41; 🗙 Xi R43	
	♦ Carc. 2, H351; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H312; Skin Sens. 1, H317	

# 4 First aid measures

• Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- *After skin contact: Generally the product does not irritate the skin.*

(Contd. on page 3)

Printing date 29.01.2015

Revision: 29.01.2015

Trade name: BETEK FLOOR PAINT

(Contd. of page 2)

- · After eye contact: Rinse opened eye for several minutes under running water.
- *After swallowing: If symptoms persist consult doctor.*

· Information for doctor:

- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

### **5** Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

## 6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions: No special measures required.
- Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

• **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

# 7 Handling and storage

- · Handling:
- *Precautions for safe handling* Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- Conditions for safe storage, including any incompatibilities • Storage:
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

(Contd. on page 4)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.01.2015

Revision: 29.01.2015

Trade name: BETEK FLOOR PAINT

(Contd. of page 3)

#### 8 Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· Control parameters

· Ingredients with limit values that require monitoring at the workplace:

#### 108-88-3 toluene

WEL Short-term value: 384 mg/m<sup>3</sup>, 100 ppm Long-term value: 191 mg/m<sup>3</sup>, 50 ppm Sk

• Additional information: The lists valid during the making were used as basis.

#### · Exposure controls

- Personal protective equipment:
- · General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.
- Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation  $\cdot$  *Material of gloves* 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

# 9 Physical and chemical properties

<ul> <li>Information on basic physical and cl</li> <li>General Information</li> </ul>	hemical properties	
· Appearance:		
Form:	Fluid	
Colour:	According to product specification	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
		(Contd. on page 5

Printing date 29.01.2015

Revision: 29.01.2015

Trade name: BETEK FLOOR PAINT

	(Contd. of page 4
Boiling point/Boiling range:	Undetermined.
Flash point:	41°C
Ignition temperature:	265°C
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	0.6 Vol %
Upper:	6.5 Vol %
Vapour pressure at 20°C:	6.6 hPa
Density at 20°C:	0.91 g/cm <sup>3</sup>
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Fully miscible.
Segregation coefficient (n-octanol/w	vater): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	36.4 %
Other information	No further relevant information available.

# 10 Stability and reactivity

· Reactivity

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

· Informat · Acute tox		cicological effects	
· LD/LC50	) values re	levant for classification:	
64742-88	-7 Solven	t naphtha (petroleum), medium aliph.	
Oral	LD50	>6500 mg/kg (rat)	
Dermal	LD50	>3000 mg/kg (rab)	
			(Contd. on page

Printing date 29.01.2015

#### Trade name: BETEK FLOOR PAINT

(Contd. of page 5)

Inhalative LC50/4 h > 14 mg/l (rat)

· Primary irritant effect:

• on the skin: No irritant effect.

- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

### **12 Ecological information**

- · Toxicity
- · Acquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

#### **13 Disposal considerations**

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

#### **14 Transport information**

· Land transport ADR/RL	D (cross-border)
-------------------------	------------------



- · ADR/RID class: 3 (F1) Flammable liquids.
- · Danger code (Kemler): 30 1263
- · UN-Number:
- · Packaging group:
- · Hazard label:
- UN proper shipping name: 1263 PAINT, special provision 640E

III 3

(Contd. on page 7)

GB

Printing date 29.01.2015

Revision: 29.01.2015

	(Contd. of pag
Tunnel restriction code	D/E
Maritime transport IMD	G:
3	
IMDG Class:	3
UN Number:	1263
Label	3
Packaging group:	
EMS Number:	F-E,S-E
Marine pollutant: Proper shipping name:	No PAINT
ICAO/IATA Class: UN/ID Number: Label Packaging group:	3 1263 3 III
Proper shipping name:	PAINT
UN "Model Regulation"	: UN1263, PAINT, 3, III
er mouer negutation	ser Warning: Flammable liquids.
Special precautions for u	
Special precautions for u	ing to Annex II of MARPOL 73/78 and the IBC Code Not applicable.
Special precautions for u Transport in bulk accord	ing to Annex II of MARPOL73/78 and the IBC Code Not applicable.
Special precautions for u	ing to Annex II of MARPOL73/78 and the IBC Code Not applicable.
Special precautions for u Transport in bulk accord Regulatory informati Safety, health and enviro	ing to Annex II of MARPOL73/78 and the IBC Code Not applicable. Fon nmental regulations/legislation specific for the substance or mixture
Special precautions for u Transport in bulk accord Regulatory informati Safety, health and enviro Labelling according to R Hazard statements	ing to Annex II of MARPOL73/78 and the IBC Code Not applicable.
Special precautions for u Transport in bulk accord Regulatory informati Safety, health and enviro Labelling according to R	ing to Annex II of MARPOL73/78 and the IBC Code Not applicable. On onmental regulations/legislation specific for the substance or mixture egulation (EC) No 1272/2008

23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

36 Wear suitable protective clothing and gloves.

46 If swallowed, seek medical advice immediately and show this container or label.

56 Dispose of this material and its container to hazardous or special waste collection point.

· National regulations:

Class	Share in %
Ι	0.4
NK	36.4

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 8)

GE

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.01.2015

Trade name: BETEK FLOOR PAINT

Revision: 29.01.2015

(Contd. of page 7)

#### **16 Other information** This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. · Relevant phrases H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H361d Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. R11 Highly flammable. R21 Harmful in contact with skin. R38 Irritating to skin. R40 Limited evidence of a carcinogenic effect. R41 Risk of serious damage to eyes. *R43* May cause sensitisation by skin contact. R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. *R63* R65 Harmful: may cause lung damage if swallowed. R67 Vapours may cause drowsiness and dizziness. · Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organization ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) GHS: Globally Harmonized System of Classification and Labelling of Chemicals LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent GB