

Preparation date: 04.01.2021 Revision: 21.02.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: BETEK MOMENTO SATIN
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Water Based Paint.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Betek Boya ve Kimya Sanayi A.S.

G.O.S.B. Tembelova Alani 3200 Sokak No:3206

41400 Gebze/ Kocaeli/ Türkiye Tel: 00 90 262 678 30 00

Fax: 00 90 262 641 21 68

busemuzeyyen.poyraz@betek.com.tr

- · Further information obtainable from: R&D Department
- 1.4 Emergency telephone number: 0090 262 678 30 00

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard statements

H317 May cause an allergic skin reaction.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves.

P362+P364 Take off contaminated clothing and wash it before reuse. P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see on this label).

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Preparation date: 04.01.2021 Revision: 21.02.2020

Trade name: BETEK MOMENTO SATIN

(Contd. of page 1)

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description:

· Dangerous components:			
CAS: 112-34-5	2-(2-butoxyethoxy)ethanol	2.5-10%	
EINECS: 203-961-6	♦ Eye Irrit. 2, H319		
CAS: 57-55-6	Propylene glycol	≤ 2.5%	
EINECS: 200-338-0	♦ Acute Tox. 4, H302		
CAS: 1336-21-6	ammonia solution 25%	≤ 2.5%	
EINECS: 215-647-6	🥎 Skin Corr. 1B, H314; 🦠 Aquatic Acute 1, H400		
CAS: 5395-50-6	üre tetrametilol astilen	≤ 2.5%	
EINECS: 226-408-0	💠 Skin Sens. 1, H317		
CAS: 55965-84-9	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	≤ 2.5%	
	Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317		

·SVHC

37205-87-1 Isononylphenol

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

• 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Preparation date: 04.01.2021 Revision: 21.02.2020

Trade name: BETEK MOMENTO SATIN

(Contd. of page 2)

5.3 Advice for firefighters

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

112-34-5 2-(2-butoxyethoxy)ethanol

WEL Short-term value: 101.2 mg/m³, 15 ppm Long-term value: 67.5 mg/m³, 10 ppm

57-55-6 Propylene glycol

WEL Long-term value: 474* 10** mg/m³, 150* ppm *total vapour and particulates **particulates

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

(Contd. on page 4)

Preparation date: 04.01.2021 Revision: 21.02.2020

Trade name: BETEK MOMENTO SATIN

(Contd. of page 3)

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and	i cnemicai properties
General Information	
Appearance:	
Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value at 20°C:	8
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling ran	ge: 100 °C
Flash point:	Not applicable.
Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density at 20 °C:	$1.35 g/cm^3$
Relative density	Not determined.
Vapour density	Not determined.

(Contd. on page 5)

Preparation date: 04.01.2021 Revision: 21.02.2020

Trade name: BETEK MOMENTO SATIN

		(Contd. of page 4
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Fully miscible.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 6)

Preparation date: 04.01.2021 Revision: 21.02.2020

Trade name: BETEK MOMENTO SATIN

(Contd. of page 5)

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

14.1 UN-Number ADR, ADN, IMDG, IATA	-	
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	-	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA Class	-	
14.4 Packing group ADR, IMDG, IATA	-	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Ann Marpol and the IBC Code	ex II of Not applicable.	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 55
- · National regulations:

Class	Share in %
Wasser	7.3
NK	5.5

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Preparation date: 04.01.2021 Revision: 21.02.2020

Trade name: BETEK MOMENTO SATIN

(Contd. of page 6)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 3: Acute toxicity - oral - Category 3

Acute Tox. 4: Acute toxicity - oral - Category 4

Acute Tox. 2: Acute toxicity - dermal - Category 2

Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1