



DECORATIVE WATER-BASED INTERIOR PRODUCT GROUP

BETEK CONTACT

DESCRIPTION

Polymer modified resin-based interior and exterior primer that is used to improve the surface adherence before plaster and cement-based plaster applications on exposed concrete.

SPECIFICATIONS

Technical Specifications:

Density: 1.49 ± 0.05 g/ml

Drying Time: 24 hours (at 20°C, 65% HR)

Application Temperature: +5°C - +30°C

APPLICATION SURFACES

Apply to brute concrete surface after plaster and cement-based mortar application. Used to improve adherence to surfaces like brute concrete wall, column, ceiling.

APPLICATION

Surface Preparation: Clean the surface from all types of dirt, rust and form oils, if any, that may prevent adherence of the product to the surface. Repair the imperfections on the surface. Ensure the surface is dry and clean.

Application: Add maximum 50% water based on the requested consistency, mix with a low speed mixer, apply on surface with sheepskin roller as a single coat. Mix regularly during application. Wait until the surface is fully dry for plaster application (approximately 24 hours).

You can access the MSDS and TDS forms including the information regarding detailed application, healthy-safety-handling risks and precautions on www.betekexport.com.

WARNING:

- Ensure the ambient temperature is between +5°C and +30°C.
- Mix regularly during application.

THINNING

Recommended to be applied in two coats after thinning by 50% with clean water in roller applications.

DRYING TIME (at 20°C, 65% HR):

Final drying: 24 hours (drying time can increase at higher relative humidity and lower temperature values).

CONSUMPTION

4 m² single coat per kilogram depending on the type, absorbency and structure of the application surface. Perform a controlled sample run to estimate the precise consumption.

STORAGE

May be stored for 3 years in its unopened packaging in a cool and dry environment protected against frosting and direct sunlight. Close the package right after application in an air-tight manner.

PACKAGING

12 Kg, 4 Kg

HAZARD DESCRIPTION

Xi Irritating.

Hazard statements

H317 May cause an allergic skin reaction

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment (see on this label).



P363 Wash contaminated clothing before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations

This technical sheet is prepared based on laboratory data under normal conditions, consult to technical personnel for details that are not provided above.

Otherwise, the manufacturing company cannot be held responsible for the failures that may arise due to lack of knowledge. Our company reserves the right to change this information.

Where necessary, please refer to Material Safety Data Sheets for more information on health, safety and handling risks and precautions associated with the products.