

Betek PVA Glue

Product Description:

54% solid polyvinyl acetate-based white glue with filler that is stabilized with polyvinyl alcohol and surfactant.

Application Areas:

Can be used safely in coating, fixing and backing all types of wood, chipboard, MDF.

Technical Specifications:

Appearance	White
Solid Ratio (%)*	54 ± 2
pH	7,0 ± 1,0
Viscosity (mPa.s)**	12500 ± 2500
Density (g/cm ³)	1.25 ± 0.02
MFFT	5 ± 1

*3 hours in 110°C-115°C

**Brookfield LVDV-II +, 20°C, Spindle 3/20 rpm

Application:

- Clean all types of dust, oil and dirt on the application surface.
- Ensure the surface temperature and the ambient temperature are above +5°C during application.
- Apply the glue in an amount that overflows from the edges of the application surface and wipe the overflowing product with a damp cloth.
- Fix after waiting maximum 10 minutes.
- The product is ready-to-use. Do not add any water.
- Close the lid of the package firmly after the application.
- Applied with brush or roller.
- After application, all used tools should be cleaned with water.
- Avoid using any rusty tool.

Dry Time:

Varies between 0.5 to 2 hours depending on the thickness of the applied film, the type of the application surface, the temperature and the humidity of the environment.

Consumption:

150-250 g/m² depending on the thickness of the applied film and the application surface.

Storage:

Can be stored for 1 year provided that its package is unopened and it is in a 0-40°C place away from sunlight. **Protect from frost.**

Hazard statements

H317 May cause an allergic skin reaction

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P321 Specific treatment (see on this label).

P363 Wash contaminated clothing before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with
local/regional/national/international regulations