

according to 1907/2006/EC, Article 31

Printing date 27.01.2015

Revision: 27.01.2015

### 1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- Trade name: BETEK CEILING PLASTIC
- · Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the preparation Water Based Paint
- Details of the supplier of the safety data sheet

Manufacturer/Supplier: Betek Boya ve Kimya Sanayi A.S.
G.O.S.B. Tembelova Alani 3200 Sokak No:3206 41400 Gebze/ Kocaeli/ Türkiye Tel: 00 90 262 678 30 00 Fax: 00 90 262 641 21 68

· Further information obtainable from: R&D Department

· Emergency telephone number: 0090 262 678 3000

### 2 Hazards identification

· Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



Skin Sens. 1 H317 May cause an allergic skin reaction.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xi; Sensitising

- *R43:* May cause sensitisation by skin contact.
- · Information concerning particular hazards for human and environment:
- The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
- · Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· Label elements

- Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



### · Signal word Warning

### · Hazard-determining components of labelling:

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one [EC no. 220-239-6] (3:1) mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1)

### • Hazard statements

H317 May cause an allergic skin reaction.

(Contd. on page 2)

according to 1907/2006/EC, Article 31

Printing date 27.01.2015

Revision: 27.01.2015

### Trade name: BETEK CEILING PLASTIC

(Contd. of page 1)

### · Precautionary statements

- *P101* If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read label before use.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- *P280 Wear protective gloves/protective clothing/eye protection/face protection.*
- *P321* Specific treatment (see on this label).
- *P363 Wash contaminated clothing before reuse.*
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- *P501 Dispose of contents/container in accordance with local/regional/national/international regulations.*
- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

### 3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.

### · Dangerous components:

 55965-84-9
 mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl 

 2Hisothiazol-3-one [EC no. 220-239-6] (3:1) mixture of: 5-chloro-2-methyl-4-isothiazolin 

 3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1)

 T R23/24/25;
 C R34;
 N R50/53

 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331;
 Skin Corr. 1B, H314;

• Additional information: For the wording of the listed risk phrases refer to section 16.

### 4 First aid measures

- · Description of first aid measures
- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- *After eye contact: Rinse opened eye for several minutes under running water.*
- After swallowing: If symptoms persist consult doctor.

### **5** Firefighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Advice for firefighters
- · Protective equipment: No special measures required.

# 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Not required.

(Contd. on page 3)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 27.01.2015

Revision: 27.01.2015

### Trade name: BETEK CEILING PLASTIC

(Contd. of page 2)

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- *Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).*
- Ensure adequate ventilation.
- **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- · Information about fire and explosion protection: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.

## 8 Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:
- Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

• Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation (Contd. on page 4)

according to 1907/2006/EC, Article 31

Revision: 27.01.2015

### Trade name: BETEK CEILING PLASTIC

(Contd. of page 3)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Goggles recommended during refilling

9 Physical and chemical properties	
<ul> <li>Information on basic physical and chemical properties</li> <li>General Information</li> <li>Appearance:</li> </ul>	
Form:	Liquid
Colour:	According to product specification
· Odour:	Characteristic
· pH-value at 20°C:	7-9
• Change in condition Melting point/Melting rang Boiling point/Boiling range	
· Flash point:	Not applicable.
· Self-igniting:	Product is not selfigniting.
• Danger of explosion:	Product does not present an explosion hazard.
· Vapour pressure at 20°C:	23 hPa
· Density at 20°C:	1.63-1.69 g/cm <sup>3</sup>
• Solubility in / Miscibility with water:	h Fully miscible.
· Solvent content: VOC (EC)	15 g/l
Solids content:	67.0 %

# 10 Stability and reactivity

· Reactivity

· Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 5)

GB

according to 1907/2006/EC, Article 31

Printing date 27.01.2015

### Trade name: BETEK CEILING PLASTIC

(Contd. of page 4)

### **11 Toxicological information**

- · Information on toxicological effects
- Acute toxicity:
- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- Sensitization: Sensitization possible through skin contact.
- Additional toxicological information: The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant
- Sensitisation May cause sensitisation by skin contact.

## **12 Ecological information**

- · Toxicity
- Acquatic toxicity: No further relevant information available.
- Additional ecological information:
- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

### **13 Disposal considerations**

- Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- *Recommendation: Disposal must be made according to official regulations.*

### **14 Transport information**

- · Land transport ADR/RID (cross-border) · ADR/RID class: -
- Maritime transport IMDG:
- · IMDG Class:
- Marine pollutant: No
- Air transport ICAO-TI and IATA-DGR: • ICAO/IATA Class: -
- · UN "Model Regulation": -
- · Special precautions for user Not applicable.

(Contd. on page 6)

GB

according to 1907/2006/EC, Article 31

Printing date 27.01.2015

Revision: 27.01.2015

Trade name: BETEK CEILING PLASTIC

(Contd. of page 5)

GR

### **15 Regulatory information**

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

- H301 Toxic if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H331 Toxic if inhaled.
- *H400 Very toxic to aquatic life.*
- *H410 Very toxic to aquatic life with long lasting effects.*

R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

- R34 Causes burns.
- *R43 May cause sensitisation by skin contact.*
- *R50/53* Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### • Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

VOC: Volatile Organic Compounds (USA, EU)