

Printing date 29.01.2015 Revision: 29.01.2015

## 1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: BETEK YACHT VARNISH
- · Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the preparation Urethane alkyd resin combined, UV resistant yacht varnish.
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Betek Boya ve Kimya Sanayi A.S.

G.O.S.B. Tembelova Alani 3200 Sokak No:3206

41400 Gebze/ Kocaeli/ Türkiye Tel: 00 90 262 678 30 00

Fax: 00 90 262 641 21 68

- · Further information obtainable from: R&D department.
- · Emergency telephone number: 0090 262 678 3000

## 2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xn; Harmful

R65: Harmful: may cause lung damage if swallowed.

R10: Flammable.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS08

· Signal word Danger

Printing date 29.01.2015 Revision: 29.01.2015

Trade name: BETEK YACHT VARNISH

(Contd. of page 1)

#### Hazard-determining components of labelling:

Solvent naphtha (petroleum), medium aliph.

· Hazard statements

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

Contains 2-butanone oxime. May produce an allergic reaction.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64742-88-7	Solvent naphtha (petroleum), medium aliph.	25-50%
EINECS: 265-191-7	<b>★</b> Xn R65	
	<b>♦</b> Asp. Tox. 1, H304	
CAS: 96-29-7	2-butanone oxime	<i>≤</i> 2.5%
EINECS: 202-496-6	<b>X</b> Xn R21-40; <b>X</b> Xi R41; <b>X</b> Xi R43	
	♦ Carc. 2, H351; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H312; Skin Sens. 1, H317	

<sup>•</sup> Additional information: For the wording of the listed risk phrases refer to section 16.

## 4 First aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

## 5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.

(Contd. on page 3)

Printing date 29.01.2015 Revision: 29.01.2015

Trade name: BETEK YACHT VARNISH

(Contd. of page 2)

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Advice for firefighters
- · Protective equipment: No special measures required.

## 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### 7 Handling and storage

- · Handling:
- Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.

## 8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 4)

Printing date 29.01.2015 Revision: 29.01.2015

Trade name: BETEK YACHT VARNISH

(Contd. of page 3)

#### · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid

Colour: According to product specification

· Odour: Characteristic

· Change in condition

Melting point/Melting range: Undetermined. Boiling point/Boiling range: Undetermined.

· Flash point:	< 40°C
· Ignition temperature:	265°C
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	0.6 Vol %
Upper:	6.5 Vol %
· Vapour pressure at 20°C:	6.6 hPa
Density at 20°C:	0.93 g/cm³

· Solubility in / Miscibility with

water:Fully miscible.Other informationVOC (in can): 438 g/l

VOC (after thinning): 517 g/l

GF

Printing date 29.01.2015 Revision: 29.01.2015

Trade name: BETEK YACHT VARNISH

(Contd. of page 4)

## 10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- LD/LC50 values relevant for classification:

### 64742-88-7 Solvent naphtha (petroleum), medium aliph.

Oral	LD50	>6500 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rab)
Inhalative	LC50/4 h	>14 mg/l (rat)

- Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

## 12 Ecological information

- · Toxicity
- · Acquatic toxicity: No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

GI

Printing date 29.01.2015 Revision: 29.01.2015

Trade name: BETEK YACHT VARNISH

(Contd. of page 5)

## 14 Transport information

· Land transport ADR/RID (cross-border)



· ADR/RID class: 3 (F1) Flammable liquids.

Danger code (Kemler): 30
UN-Number: 1993
Packaging group: III
Hazard label: 3

· UN proper shipping name: 1993 FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE), special

provision 640E

· Maritime transport IMDG:



· IMDG Class: 3
· UN Number: 1993
· Label 3
· Packaging group: III
· EMS Number: F-E,S-E
· Marine pollutant: No

• Proper shipping name: FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE)

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 3
 · UN/ID Number: 1993
 · Label 3
 · Packaging group: III

· Proper shipping name: FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE)

- · UN "Model Regulation": UN1993; FLAMMABLE LIQUID, N.O.S.; 3; III
- · Special precautions for user Warning: Flammable liquids.

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · National regulations:

Class	Share in %
Ι	0.4
NK	34.6

(Contd. on page 7)

Revision: 29.01.2015 Printing date 29.01.2015

Trade name: BETEK YACHT VARNISH

(Contd. of page 6)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H351 Suspected of causing cancer.

R21 Harmful in contact with skin.

R40 Limited evidence of a carcinogenic effect.

R41 Risk of serious damage to eyes.

R43 May cause sensitisation by skin contact.

R65 Harmful: may cause lung damage if swallowed.

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) GHS: Globally Harmonized System of Classification and Labelling of Chemicals

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent



Printing date 29.01.2015 Revision: 29.01.2015

## 1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: BETEK SEMI GLOSS YACHT VARNISH
- · Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the preparation Urethane resin combined, UV resistant yacht varnish.
- Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Betek Boya ve Kimya Sanayi A. Ş.

G.O.S.B. Tembelova Alanı 3200 Sokak No: 3206

41400 Gebze/ Kocaeli/ Türkiye

Tel: 00 90 262 678 30 00 Fax: 00 90 262 641 21 68

- · Further information obtainable from: R&D Department
- · Emergency telephone number: 0090 262 678 3000

## 2 Hazards identification

- · Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Carc. 1B H350 May cause cancer.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xn; Harmful

R65: Harmful: may cause lung damage if swallowed.

Flammable. Repeated exposure may cause skin dryness or cracking.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 29.01.2015 Revision: 29.01.2015

Trade name: BETEK SEMI GLOSS YACHT VARNISH

(Contd. of page 1)

#### · Hazard pictograms



· Signal word Danger

## · Hazard-determining components of labelling:

Solvent naphtha (petroleum), medium aliph. Naphtha (petroleum), hydrotreated heavy

· Hazard statements

H226 Flammable liquid and vapour.

H350 May cause cancer.

H304 May be fatal if swallowed and enters airways.

Contains 2-butanone oxime. May produce an allergic reaction.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64742-88-7	Solvent naphtha (petroleum), medium aliph.	25-50%
EINECS: 265-191-7	<b>★</b> Xn R65	
	<b>♦</b> Asp. Tox. 1, H304	
	Naphtha (petroleum), hydrotreated heavy	<i>≤</i> 2.5%
EINECS: 265-150-3		
	� Carc. 1B, H350; Asp. Tox. 1, H304	
CAS: 96-29-7	2-butanone oxime	<i>≤</i> 2.5%
EINECS: 202-496-6	🗙 Xn R21-40; 🗶 Xi R41; 🗙 Xi R43	
	♦ Carc. 2, H351; ♦ Eye Dam. 1, H318; ♦ Acute Tox. 4, H312; Skin Sens. 1, H317	

· Additional information: For the wording of the listed risk phrases refer to section 16.

GB

Printing date 29.01.2015 Revision: 29.01.2015

Trade name: BETEK SEMI GLOSS YACHT VARNISH

(Contd. of page 2)

## 4 First aid measures

- Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

## 5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

## 8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

Revision: 29.01.2015 Printing date 29.01.2015

Trade name: BETEK SEMI GLOSS YACHT VARNISH

(Contd. of page 3)

- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- General Information
- · Appearance:

Fluid Form:

Colour: According to product specification

Odour: Characteristic

· Change in condition

Melting point/Melting range: Undetermined. **Boiling point/Boiling range:** Undetermined.

· Flash point: < 40°C 265°C · Ignition temperature:

· Self-igniting:

Product is not selfigniting.

(Contd. on page 5)

Printing date 29.01.2015 Revision: 29.01.2015

Trade name: BETEK SEMI GLOSS YACHT VARNISH

	(Contd. of page 4)
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	0.6 Vol %
Upper:	6.5 Vol %
· Vapour pressure at 20°C:	6.6 hPa
· Density at 20°C:	0.91 g/cm³
Solubility in / Miscibility with water:	Fully miscible.

## 10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:

	· LD/LC50 values relevant for classification:		
64742-88-7 Solvent naphtha (petroleum), medium aliph.			aphtha (petroleum), medium aliph.
	Oral	LD50	>6500 mg/kg (rat)
	Dermal	LD50	>3000 mg/kg (rab)
	Inhalative	LC50/4 h	>14 mg/l (rat)
	64742-48-9 Naphtha (petroleum), hydrotreated heavy		
	Oral	LD50	>5000 mg/kg (rat)
	Dermal	LD50	>3000 mg/kg (rab)

- · Primary irritant effect:
- on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

## 12 Ecological information

- · Toxicity
- · Acquatic toxicity: No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

(Contd. on page 6)

Printing date 29.01.2015 Revision: 29.01.2015

Trade name: BETEK SEMI GLOSS YACHT VARNISH

(Contd. of page 5)

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

## 14 Transport information

· Land transport ADR/RID (cross-border)



· ADR/RID class: 3 (F1) Flammable liquids.

Danger code (Kemler): 30
UN-Number: 1993
Packaging group: III
Hazard label: 3

· UN proper shipping name: 1993 FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE), special

provision 640E

· Maritime transport IMDG:



· IMDG Class: 3
· UN Number: 1993
· Label 3
· Packaging group: III
· EMS Number: F-E,S-E
· Marine pollutant: No

· Proper shipping name: FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE)

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 3
· UN/ID Number: 1993
· Label 3
· Packaging group: III

(Contd. on page 7)

Printing date 29.01.2015 Revision: 29.01.2015

Trade name: BETEK SEMI GLOSS YACHT VARNISH

(Contd. of page 6)

- Proper shipping name: FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE)
- · UN "Model Regulation": UN1993, FLAMMABLE LIQUID, N.O.S., 3, III
- · Special precautions for user Warning: Flammable liquids.

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · National regulations:

Class	Share in %
Ι	0.2
NK	48.3

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H350 May cause cancer.

H351 Suspected of causing cancer.

R21 Harmful in contact with skin.

R40 Limited evidence of a carcinogenic effect.

R41 Risk of serious damage to eyes.

R43 May cause sensitisation by skin contact.

R45 May cause cancer.

R65 Harmful: may cause lung damage if swallowed.

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent